

SAFETY EYEWEAR

SAFETY SERIES INSTRUCTIONS FOR USE

(F 2797 EN166:2001

BSI Group The Netherlands B.V., (NB2797). BSI Group The Netherlands B.V., Say Building, John M. Keynesplein 9, 1066 EP, Amsterdam, Netherlands.

- OX-S248101 OX Professional Wrap Around Safety Glasses Clear
- OX-S248102 OX Professional Wrap Around Safety Glasses Smoked OX-S241701 OX Safety Glasses Clear OX-S241702 OX Safety Glasses Smoked

- OX-S248301 **OX Visitor Safety Spectacles**
- OX-S244601 OX Direct Vent Safety Goggles OX Indirect Vent Safety Goggle
- OX-S244701
- OX-S245201 OX Deluxe Anti Mist Safety Goggles

WARNING:

- If the symbols F, B and A are not common to both the ocular and frame then it is the lower level which shall be assigned to the complete eye-protector
- If lens becomes scratched or damaged the eye protector should be replaced.
- The frame, when in contact with the skin may cause allergic reactions to susceptible individuals, if this is the case doctor's advice should be consulted.
- The housings of these eye protectors provide less protection against impact than the lens.
- These eye protectors may transmit impacts to eye-wear enclosed by the eye protector

USE:

- In use, ensure the eye protector fits comfortably over the eyes.
 Under normal circumstances the eye protector should offer adequate protection for 5 years.

STORAGE AND MAINTENANCE:

- When not in use or during transportation this eye protector should be stored in a container such that it is out of direct sunlight, away from chemicals and abrasive substances and cannot be damaged by physical contact with hard surfaces/items
- To clean/disinfect, rinse in 1% solution of mild detergent and dry with a soft cloth.
- DO NOT USE abrasive cleaners.

EN166	The European Standard for Industrial Eye Protection	CE	Conformity to European
#	Welding filter grade # (EN169)		legislation 2016/425
2 OR 2C-#	Ultra violet filter (C = good colour recognition) & grade # (EN170)		The ANSI Standard for Industrial
4-#	Infrared filter performance & grade # (EN171)	Z87	Eye Protection
5-#	Sunglare filter performance & grade # (EN172)	- +	The eye protector is impact rated The eye protector has been
OX	Manufacturers Trademark		designed to suit a small head
1	Number signifying the optical class, 1 is high 3 is low	- W#	Welding filter & grade #
s	Meets the requirements for increased robustness		UV filter & grade #
F		L#	Visible light filter & grade #
-	Withstands low energy impact from highspeed particles		IR filter & grade #
В	Withstands medium energy impact from high speed particles	v	Variable tint
т	If protection at extremes of temperature is required select eyewear including a T after the impact marking	s	Special purpose lenses
3	Protection against liquid droplets	D3	Protection against liquid droplets
4	Protection against large dust particles	D4	Protection against large dust
5	Protection against gases and fine particles		particles
8	Resistant to short circuit electric arc	D5	Protection against fine particles
9	Resistant to molten metals	TP TC 019/2011	The Technical Regulation of the Eurasian Union on Safety of PPE
N	EN166 resistance to fogging/misting	E HU	Conformity to the Technical Regulation
к	EN166 resistance to surface damage by fine particles	*	Anti-scratch/anti-mist coated
н	The eye protector has been designed to suit a small head	X	Dispose of in accordance with local legislation



OR or visit our

Manufacturer Address

OX Products Group UK Ltd. Unit 2 Riverside, Kangley Bridge Road, London SE26 5DA United Kingdom Tel: 0044 (0)20 8676 9990 Fax: 0044 (0)20 8676 7520 sales.uk@oxtools.com www.oxtools.com

> OEM Product - Authorised by JSP Ltd Our Safety Eyewear are in conformity with the PPE Regulations (EU)2016/425.