

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

BOSTIK J100 SMOOTH FINISH GROUT WHITE

Supercedes Date: 26-Jul-2021

Revision date 05-Jan-2022 Revision Number 2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name BOSTIK J100 SMOOTH FINISH GROUT WHITE

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Cement. Sealant.
Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name
Bostik Limited
Common Rd
ST16 3EH
Stafford UK

Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom +44 (1785) 272650

Ireland +353 (1) 8624900 (Monday- Friday 9am-5pm)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 1 - (H318)
Specific target organ toxicity — single exposure	Category 3 - (H335)

2.2. Label elements

Contains Cement Portland White



Signal word Danger

Hazard statements

H315 - Causes skin irritation.

H318 - Causes serious eye damage.

H335 - May cause respiratory irritation.

EU Specific Hazard Statements

United Kingdom - BE Page 1 / 11

BOSTIK J100 SMOOTH FINISH GROUT WHITE

Supercedes Date: 26-Jul-2021

Revision date 05-Jan-2022 Revision Number 2

EUH208 - Contains 2-octyl-2H-isothiazol-3-one [OIT]. May produce an allergic reaction

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

P260 - Do not breathe dust

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves and eye/face protection

P302 + P352 - IF ON SKIN: Wash with plenty of water and soap

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor

P362 + P364 - Take off contaminated clothing and wash it before reuse

P405 - Store locked up

P501 - Dispose of contents/ container to an approved waste disposal plant

2.3. Other hazards

When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when kneeling in wet cement even when wearing trousers. Frequent inhalation of large quantities of cement dust over a long period of time increases the risk of developing lung disease. Product dust may be irritating to eyes, skin and respiratory system. Repeated exposure may cause skin dryness or cracking.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Cement Portland White	266-043-4	65997-15-1	40 - <80	STOT SE 3 (H335) Skin Irrit. 2 (H315) Eye Dam. 1 (H318)		Exempt
2-octyl-2H-isothiazol-3-o ne [OIT]	247-761-7	26530-20-1	0.01 - <0.1	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) Skin Corr. 1B (H314) Eye Dam 1 (H318) Skin Sens. 1A (H317) Aquatic Acute 1	^	-

United Kingdom - BE Page 2 / 11

BOSTIK J100 SMOOTH FINISH GROUT WHITE

Supercedes Date: 26-Jul-2021 Revision Number 2

	(H400)	
	Aquatic Chronic	
	1 (H410)	
	M Factor Acute	
	=10	
	M Factor Chronic	
	= 1	

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice If medical advice is needed, have product container or label at hand.

Inhalation Remove to fresh air. Get medical attention immediately if symptoms occur. IF exposed

or concerned: Get medical advice/attention.

Eye contact Do not rub affected area. Immediately flush with plenty of water. After initial flushing,

remove any contact lenses and continue flushing for at least 15 minutes. Consult an

Revision date 05-Jan-2022

ophthalmologist.

Skin contact Brush off loose particles from skin. Remove material from skin immediately. Take off

contaminated clothing and wash it before reuse.

Ingestion Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce

vomiting. Call a doctor.

Self-protection of the first aider Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section

8).

4.2. Most important symptoms and effects, both acute and delayed

Symptoms Burning sensation. Causes serious eye damage. Irritating to skin. Inhalation of dust in

high concentration may cause irritation of respiratory system. When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g.

when kneeling in wet cement even when wearing trousers.

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

surrounding environment.

Unsuitable extinguishing media Full water jet.

United Kingdom - BE Page 3 / 11

BOSTIK J100 SMOOTH FINISH GROUT WHITE

Supercedes Date: 26-Jul-2021

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the No information available.

chemical

5.3. Advice for firefighters

precautions for fire-fighters

Special protective equipment and Firefighters should wear self-contained breathing apparatus and full firefighting turnout

Revision date 05-Jan-2022

Revision Number 2

gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid generation of dust. Do not get in eyes, on skin, or on clothing. Use personal

protective equipment as required.

Refer to protective measures listed in Sections 7 and 8. Other information

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil.

6.3. Methods and material for containment and cleaning up

Methods for containment Cover powder spill with plastic sheet or tarp to minimise spreading and keep powder dry.

Prevent dust cloud.

Methods for cleaning up Do not dry sweep dust. Wet dust with water before sweeping or use a vacuum to collect

dust. Use appropriate personal protective equipment (PPE). Carefully shovel or sweep

up spilled material and place in suitable container. Avoid generating dust.

Clean contaminated objects and areas thoroughly observing environmental regulations. Prevention of secondary hazards

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Ensure adequate ventilation. Avoid generation of dust. Avoid contact with skin, eyes or Advice on safe handling

clothing. Use personal protection equipment. Take off contaminated clothing and wash it

before reuse.

General hygiene considerations Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection.

Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. **Storage Conditions**

Keep out of the reach of children. Keep the packing dry and well sealed to prevent

contamination and absorption of humidity.

Recommended storage

temperature

Keep at temperatures between 2 and 10 °C.

7.3. Specific end use(s)

United Kingdom - BE Page 4/11

Revision date 05-Jan-2022

BOSTIK J100 SMOOTH FINISH GROUT WHITE

Supercedes Date: 26-Jul-2021 Revision Number 2

Specific use(s) Sealant. Cement.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	United Kingdom
Cement Portland White	-	STEL: 30 mg/m ³
65997-15-1		STEL: 12 mg/m ³
		TWA: 10 mg/m³ (inhalable)
		TWA: 4 mg/m³ (respirable)
Dust	-	TWA: 10 mg/m ³
RR-12364-8		TWA: 4 mg/m ³
		STEL: 30 mg/m ³
		STEL: 12 mg/m ³

Derived No Effect Level (DNEL) No information available

Predicted No Effect Concentration No information available. **(PNEC)**

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be

exhausted directly at the point of origin.

Personal protective equipment

Eye/face protectionTight sealing safety goggles. Face protection shield. Wear safety glasses with side

shields (or goggles). Eye protection must conform to standard EN 166.

Hand protection For operations where prolonged or repeated skin contact may occur, impervious gloves

should be worn. Gloves made of plastic or rubber. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Gloves must conform

to standard EN 374.

Skin and body protection Wear appropriate personal protective clothing to prevent skin contact. Avoid contact with

skin, eyes or clothing.

Respiratory protection Avoid generation of dust. Ensure adequate ventilation, especially in confined areas. No

protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Possible nuisance dust.

Recommended filter type: Particle filter device (DIN EN 143). with filter for particulates. Wear a respirator

conforming to EN 140 with Type P2/P3 filter or better.

Environmental exposure controls Do not allow into any sewer, on the ground or into any body of water.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Solid

United Kingdom - BE Page 5 / 11

Revision date 05-Jan-2022

Revision Number 2

BOSTIK J100 SMOOTH FINISH GROUT WHITE

Supercedes Date: 26-Jul-2021

Appearance Powder Colour White Odour Odourless

Odour threshold No information available

Property Values Remarks • Method

pH No data available pH (as aqueous solution) 11 - 14

Melting point / freezing point Not applicable . °C Initial boiling point and boiling Not applicable . °C

range

Flash point

Evaporation rate

Flammability

Flammability

Not applicable . °C

Not applicable .

No data available

Flammability Limit in Air

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

Vapour pressureNo data availableRelative vapour densityNo data availableRelative densityNo data available

Water solubility Cement based products react and

solidify in contact with water

Solubility(ies) No data available **Partition coefficient** No data available **Autoignition temperature** No data available **Decomposition temperature** No data available Kinematic viscosity Not applicable . **Dynamic viscosity** Not applicable . **Explosive properties** No data available **Oxidising properties** No data available

9.2. Other information

Solid content (%) 100
Softening Point Not relevant

VOC Content (%)

Density 1.6 g/ml

Bulk density 1.1 50-1000 μm

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Product cures with moisture.

10.2. Chemical stability

Stability Keep away from Incompatible materials. Stable under recommended storage conditions.

Explosion data

Sensitivity to mechanical

mpact

None.

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

United Kingdom - BE Page 6 / 11

BOSTIK J100 SMOOTH FINISH GROUT WHITE

•

10.4. Conditions to avoid

Supercedes Date: 26-Jul-2021

Conditions to avoid Product cures with moisture.

10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidising agents. Acids. Aluminium.

10.6. Hazardous decomposition products

Hazardous decomposition

products

None under normal use conditions. Stable under recommended storage conditions.

Revision date 05-Jan-2022

Revision Number 2

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. May cause irritation of

respiratory tract.

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye

damage. May cause irreversible damage to eyes.

Skin contact Specific test data for the substance or mixture is not available. Causes skin irritation.

(based on components).

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause

gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Redness. Burning. May cause blindness. May cause redness and tearing of the eyes.

Numerical measures of toxicity

Acute toxicity

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Cement Portland White 65997-15-1	>2000 mg/Kg	>2000 mg/Kg	
2-octyl-2H-isothiazol-3-one	=125 mg/kg (Rattus)	= 690 mg/kg (Oryctolagus cuniculus)	
26530-20-1		3434,	

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Irritating to skin.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes burns. Risk of serious

damage to eyes.

United Kingdom - BE Page 7 / 11

Revision date 05-Jan-2022

Revision Number 2

BOSTIK J100 SMOOTH FINISH GROUT WHITE

Supercedes Date: 26-Jul-2021

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure May cause respiratory irritation.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met. **Aspiration hazard**

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
2-octyl-2H-isothiazol-3- one [OIT] 26530-20-1	0.084 mg/L	LC50 (96h) = 0.036 mg/L (Oncorhynchus mykiss) (OECD 203)		EC50 (48h) =0.42 mg/L (OECD 202)	10	1

12.2. Persistence and degradability

No information available. Persistence and degradability

Component Information				
2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)				
Method	Exposure time	Value	Results	
OECD Test No. 309: Aerobic		Half-life 0.6-1.4 d	Readily biodegradable	
Mineralization in Surface Water -				
Simulation Biodegradation Test				

12.3. Bioaccumulative potential

United Kingdom - BE Page 8/11

Revision date 05-Jan-2022

Revision Number 2

BOSTIK J100 SMOOTH FINISH GROUT WHITE

Supercedes Date: 26-Jul-2021

Bioaccumulation No information available.

Component Information

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
2-octyl-2H-isothiazol-3-one [OIT]	2.92	-
26530-20-1		

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product does not contain any substance(s) classified as PBT or vPvB.

Chemical name	PBT and vPvB assessment
2-octyl-2H-isothiazol-3-one [OIT]	The substance is not PBT / vPvB
26530-20-1	

12.6. Other adverse effects

Other adverse effects No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused

products

Dispose of in accordance with local regulations. Dispose of waste in accordance with

environmental legislation.

Contaminated packaging Do not reuse empty containers.

European Waste Catalogue 17 09 04 mixed construction and demolition wastes other than those mentioned in 17 09

01, 17 09 02 and 17 09 03

10 13 06 particulates and dust (except 10 13 12 and 10 13 13)

Cured product can be treated as construction waste. In the management of larger

quantities consult with local authorities and local waste disposal company

10 13 14 waste concrete and concrete sludge

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID numberNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing groupNot regulated14.5 Environmental hazardsNot applicable14.6 Special ProvisionsNone

IMDG

14.1 UN number or ID number
14.2 Proper Shipping Name
14.3 Transport hazard class(es)
Not regulated
Not regulated
Not regulated

United Kingdom - BE Page 9 / 11

BOSTIK J100 SMOOTH FINISH GROUT WHITE

Supercedes Date: 26-Jul-2021 Revision Number 2

Revision date 05-Jan-2022

--

14.4 Packing group Not regulated

14.5 Marine pollutant NP14.6 Special Provisions None

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID numberNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing groupNot regulated14.5 Environmental hazardsNot applicable

14.6 Special Provisions None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

United Kingdom - BE Page 10 / 11

BOSTIK J100 SMOOTH FINISH GROUT WHITE

Supercedes Date: 26-Jul-2021

Revision date 05-Jan-2022 Revision Number 2

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H301 - Toxic if swallowed

H311 - Toxic in contact with skin

H314 - Causes severe skin burns and eye damage

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H331 - Toxic if inhaled

H335 - May cause respiratory irritation

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

Legend

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Ceiling Limit Value
* Skin designation

SVHC Substance(s) of Very High Concern

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals vPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

EWC European Waste Catalogue

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 05-Jan-2022

Indication of changes

Revision note Not applicable.

Training Advice No information available

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

United Kingdom - BE Page 11 / 11