

QuickPrime™ Plus

1. Description

The Firestone QuickPrime™ Plus is designed to clean and prime the RubberCover™ EPDM membrane and/or substrate that are to receive a QuickSeam™ product. The primer activates the surface of the membrane and is necessary for the seam quality. QuickPrime Plus must be applied with a QuickScrubber™ pad and handle.



2. Preparation

Surfaces that will receive QuickPrime Plus must be clean, smooth, dry and free of sharp edges, loose materials, oil, grease and other contaminants. The mating surface of the RubberCover™ EPDM membrane shall be cleaned with a brush or clean rag. Pre-cleaning may be required. Stir the primer before and during use to achieve a uniform mix with no sediments on the bottom and no marbling evident. Restore the primer to room temperature prior to use if exposed to cold temperatures (< 15°C). Pour the required amount of QuickPrime Plus into a bucket for ease of application.

3. Application

Apply QuickPrime Plus to the RubberCover EPDM surfaces and/or other substrates to receive QuickSeam products with the QuickScrubber pad and handle, using long back and forth strokes with moderate to heavy pressure along the length of the area until surfaces become dark grey, with no streaking or puddling. Allow the primed surfaces to dry completely (usually less than 10 minutes) before applying a QuickSeam product. Refer to the Firestone guidelines for specific installation instructions.

4. Coverage

The following rates can be achieved with 1 can (0.95 l):

- QuickSeam SA Flashing: 8 lm - 1 side.
- QuickSeam Corner Flashing: 50 pieces - 1 side.
- QuickSeam Cover Strip: 20 lm - 1 side.

5. Characteristics

Technical	
• Base	Synthetic rubber polymers
• Color	Black or transparent
• Solvents	Hydrocarbons, toluene
• Solids	16 % - 18 %
• Viscosity	Very thin, free-flowing
• Specific gravity	0.79 g/cm ³
• Flash point	-4°C

6. Packaging/ Storage/ Shelf Life / Disposal

Packaging	0.95 l (¼ US gallon) pail – 12 pails per carton
Part Number	W56RAC1695 / W56RAC1695EU (0.95 l)

Storage: Store in original unopened pails at moderate temperatures (15°C - 25°C) in a dry, well-ventilated area. Keep away from heat, sparks and open flame. Protect from direct sunlight. If necessary, use an insulated box to maintain the product at moderate temperatures during transport to the job site, before and during application. This will assure the appropriate viscosity, efficiency and performance of the primer.

Technical Information Sheet



Shelf life: 12 months can be expected if stored in above-mentioned conditions. Verify production date on each pail. Shelf life will be reduced if exposed to higher temperatures. Shelf life information is only a recommendation and not a fact of life. The real expiration date highly depends on the history of storage and handling of the product. Once opened, use within 48 hours.

Disposal: Make sure that the pail is empty prior to disposal. Primer cannot be disposed in drains.

7. Precautions

Refer to Safety Data Sheet. Flammable. Keep away from fire, open flame and other possible ignition sources during storage and use. Do not smoke when using. For professional use only. Use only in well-ventilated areas. Keep pail closed when not in use. Avoid prolonged inhalation and contact with skin and eyes. Do not contaminate with foreign materials. Keep out of reach from children. Thinning is not allowed.

This document replaces any other document published previously. This sheet is meant to highlight Firestone product information based on latest knowledge and experience and is subject to change without notice (check the Firestone website for latest document version). Above mentioned values are based on tested samples and may vary within applicable tolerances. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications. No Firestone representative is authorized to vary this disclaimer.